

**IDAHO COUNTY ROAD DEPT.**  
**4682 Highway 13 Kooskia, Id 83539**  
**PHONE: 208-926-4471 FAX: 208-926-7721**  
**[lcroads2@qroidaho.net](mailto:lcroads2@qroidaho.net)**

**The Idaho County Road Department will be accepting bids for the purchase and delivery of 29,000 tons of crushed aggregate. Bids must be turned into Kathy Ackerman, Idaho County Clerk, 320 West Main Room 5, Grangeville, Idaho 83530 by March 7, 2017 at 9:00 A.M. and will be opened at 10:00 A.M. that day. Idaho County requests that the bid be submitted to include pricing with both the contractor hauling and without hauling.**

**If the contractor's source for crushing and stock piling is at a location that is advantageous to the County, the County may elect to stock pile at that location. Stock piles must be within a secured area.**

**Contractor shall provide a way to take samples and quality control to check for proper rock specifications. The Contractor shall provide the County with copies of reports.**

**Bid price will be available to other public agencies in the Kooskia area.**

**Any reject material produced during the production of the County's material will be retained by the County.**

**A 5% bid bond is required. The contract is to be completed by May 5, 2017, or bond will be forfeited.**

**The appropriate Public Works Contractors License shall be required.**

**Questions contact Gene Meinen Road Supervisor 208-926-4471.**

**\*Kidder-Harris Highway District has expressed interest in purchasing 15,000+ tons of combined products, i.e maintenance, chip seal. Contact Terry Agee for details 208-926-0176 or 208-935-5759.**

<b>Material</b>	<b>Quantity</b>	<b>Stockpile</b>
<b>5/8" maintenance</b>	<b>12,000 tons</b>	<b>Clear Creek</b>
<b>5/8 seal coat</b>	<b>5,000 tons</b>	<b>Clear Creek</b>
<b>1/2 inch plant mix</b>	<b>4,000 tons</b>	<b>County Shop</b>
<b>1/2 inch sanding material</b>	<b>6,000 tons</b>	<b>County Shop</b>
<b>3 inch material</b>	<b>2,000 tons</b>	<b>County Shop</b>
<b>Reject material</b>		

### **Specifications**

<b>5/8 maintenance</b>	<b>5/8 seal coat</b>	<b>1/2 Plant Mix</b>	<b>Sanding</b>
<b>5/8 100%</b>	<b>5/8 100 %</b>	<b>1/2 100%</b>	<b>1/2 100%</b>
<b>1/2 90 100%</b>	<b>1/2- 95-100 %</b>	<b>#4 55-70 %</b>	<b>3/8 60-90%</b>
<b>#4- 45-79 %</b>	<b>3/8 75-90 %</b>	<b>#8 45-55 %</b>	<b>4 0-10 %</b>
<b>#8 30-50 %</b>	<b>#4 30-50 %</b>	<b>30 12-30 %</b>	<b>8 0-10 %</b>
<b>30 15-30 %</b>	<b># 8 15-30 %</b>	<b>200 3-9 %</b>	
<b>200 10-16 %</b>	<b>200 2-9 %</b>		
<b>SE30</b>	<b>SE 50</b>	<b>SE 50</b>	

### **3 inch**

<b>3 100%</b>
<b>#4 20-50 %</b>